

Dehumidification Equipment



DHP Dehumidification PAC Units DHP4500P3 Technical Data


Technical Specifications

	DHP4500-100P3	DHP4500-125P3	DHP4500-190P3
DESIGN TO SUIT STANDARD CONDITIONS IN	PERTH/ ADELAIDE	MELBOURNE/ SYDNEY	BRISBANE/ NTH QLD
Nominal Airflow			
Supply Air (l/sec)	4500	4500	4500
Fresh Air (l/sec)	4500	4500	4500
Condensor Air (l/sec)	8000	10000	15200
Compressor Capacity (kW)	100	125	190
Supply Fan			
Fan Type	Plug Fan	Plug Fan	Plug Fan
Fan Motor	EC Motor	EC Motor	EC Motor
Motor Power (Watts)	2824	2825	2825
External Static (Pa)	250	250	250
Fan Diameter (mm)	450	450	450
Number of Fans	2	2	2
Condenser Fan			
Fan Type	Axial Fan	Axial Fan	Axial Fan
Fan Motor	EC Motor	EC Motor	EC Motor
Motor Power (Watts)	1950	1950	1950
Number of Fans	2	2	3
Condensor Fan Control	Head Pressure Controlled	Head Pressure Controlled	Head Pressure Controlled
Electrical			
Supply Fan FLA (A)	13.6 - 13.6 - 13.6	13.6 - 13.6 - 13.6	13.6 - 13.6 - 13.6
Condenser Fan FLA (A)	6.2 - 6.2 - 6.2	6.2 - 6.2 - 6.2	9.3 - 9.3 - 9.3
Compressor Current (A)	54 - 54 - 54	65 - 65 - 65	94 - 94 - 94
Nominal Run Current (A)	73.8 - 73.8 - 73.8	84.8 - 84.8 - 84.8	116.9 - 116.9 - 116.9
Maximum Run Current (A)	90 - 90 - 90	104 - 104 - 104	158 - 158 - 158
Volt/Phase	415V/3ph	415V/3ph	415V/3ph
Switchboard	Yes	Yes	Yes
Circuit Breakers	Yes	Yes	Yes
Controls			
0-10V DC (Supply Fan Control)	Included	Included	Included
0-10V DC (Compressor Capacity)	Included	Included	Included
Compressor Fault	Low Level	Low Level	Low Level
Fan Fault Signal	24V Output	24V Output	24V Output
Fan Status	Optional	Optional	Optional
Bypass Supply Air Damper	Included	Included	Included
Compressor Enable 24V	Included	Included	Included
PC-20CC Low Level Controller	Optional	Optional	Optional
PC-30CC High Level Controller	Optional	Optional	Optional

Technical Specifications

	DHP4500-100P3	DHP4500-125P3	DHP4500-190P3
DESIGN TO SUIT STANDARD CONDITIONS IN	PERTH/ ADELAIDE	MELBOURNE/ SYDNEY	BRISBANE/ NTH QLD
Heat Exchanger			
	*Rated at standard conditions of 35.5° db/24.0° wb		
Sensible Media	Standard	Standard	Standard
Face Velocity (m/sec)	2.38	2.38	2.38
Media Access	Removable	Removable	Removable
Pressure Drop (Pa)	130	130	130
Cabinet Construction			
Colourbond Casing	50mm Panel	50mm Panel	50mm Panel
Galvanised Base	100x50	100x50	100x50
Design Temperatures			
Ambient Summer (DB/WB)	40°C/27°C	35°C/24°C	35°C/27°C
Supply Air Summer (DB/WB)	24°C/17°C	24°C/17°C	24°C/17°C
Supply Air Moisture Content (g/kg)	9.4	9.4	9.4
Ambient Winter (DB)	5°C	3°C	5°C
Supply Air Winter (DB)	21°C	21°C	21°C
Coil Selection			
Indoor Coil Circuits	2	2	3
Face Velocity (m/sec)	2.3	2.3	2.3
Coil Coating	Included	Included	Included
Drain Tray	Stainless Steel	Stainless Steel	Stainless Steel
Compressor Details			
Total Cooling Capacity (kW)	100	125	190
Sensible Capacity (kW)	84	71	75
Latent Capacity (kW)	16	54	115
No. of Compressor	2	2	3
Compressor Type	Inverter 10-100% Capacity	Inverter 10-100% Capacity	Inverter 10-100% Capacity
Refrigerant Gas	R410A	R410A	R410A
Expansion Device	Electronic EV	Electronic EV	Electronic EV
Total Heating Capacity (kW)	67	65	100
Filters			
Filter Type	F5 Deep Bed Filter	F5 Deep Bed Filter	F5 Deep Bed Filter
Number of Filters / Size	5/600 x 600 x 380d	5/600 x 600 x 380d	5/600 x 600 x 380d
Option			
Corrosion Resistant Lining	Available	Available	Available

Fan Performance Data



Sound Power Levels

*Sound power levels at 650 Pa Total Static Pressure and 4500 L/s Total Air Volume

Inlet Rating dB		Outlet Rating dB	
63 Hz	70.4	63 Hz	75.9
125 Hz	66.9	125 Hz	69.3
250 Hz	76	250 Hz	77.8
500 Hz	74.7	500 Hz	76.8
1K Hz	71.2	1K Hz	79.3
2K Hz	73.6	2K Hz	79.1
4K Hz	76.5	4K Hz	80.8
8K Hz	74.1	8K Hz	77.5
LwA	81.4	LwA	86.2

